

TPU LAYFLAT HOSE

LAYFLAT HOSE



Construction:

Inner and cover:TPU

Reinforcement: Woven Polyester jacket

Application:

Fire-fighting, shipping, petroleum, Chemical industry,
Agriculture,Mining

Characteristic:

- High-resistance abrasion,oil resistance,
- Acid and alkali resistance, corrosion resistance,
- cold resistance, small flow resistance

Temperature: -55℃ (-131 ℉) to 80℃ (+176 ℉)

Item Code	I.D		Wall Thickness	W.P		B.P		kg	M ³	L
	Inch	mm	mm	Mpa	PSI	Mpa	PSI	(kg/m)	m ³	m
TPU050	2	51	2.6	1.0	145	3	435	0.55	0.282	200
TPU050	2	51	3.0	1.6	232	4.8	696	0.65	0.287	200
TPU065	2 1/2	65	2.6	1.0	145	3.0	435	0.65	0.399	200
TPU065	2 1/2	65	3.0	1.6	232	4.8	696	0.75	0.402	200
TPU076	3	76	2.8	1.0	145	3.0	435	0.6	0.462	200
TPU076	3	76	3.5	1.6	232	4.8	696	1.2	0.471	200
TPU080	3 1/6	80	2.8	1.6	232	4.8	696	1.0	0.486	200
TPU080	3 1/6	80	2.8	2.8	406	8.4	1218	1.3	0.486	200
TPU102	4	102	3.2	1.0	145	3.0	435	1.2	0.690	200
TPU102	4	102	3.5	1.2	145	3.6	435	1.4	0.693	200
TPU102	4	102	4.4	1.6	232	4.8	696	1.45	0.713	200
TPU102	4	102	4.6	2.0	290	6.0	870	1.5	0.794	200
TPU102	4	102	4.8	2.8	406	8.4	1218	1.8	0.880	200
TPU125	5	125	3.5	1.0	145	3.0	435	1.21	0.842	200
TPU125	5	125	3.7	1.6	232	4.8	696	1.31	0.939	200
TPU152	6	152	3.9	1.0	145	3.0	435	1.8	1.137	200
TPU152	6	152	4.0	1.4	203	4.2	609	2.03	1.137	200
TPU152	6	152	4.5	1.6	232	4.8	696	2.25	1.141	200